

SC25 Direct-input Modules

The SC25 is a two-channel direct-input card.

It is packaged in a 3U (5.25") high, 220 mm (8.7") deep, module.

TYPICAL APPLICATIONS

Voltage measurements
General-purpose data acquisition



Options with BNC or LEMO connectors

FEATURES

- Supports two ADC channels
- Provides direct connection from the front panel connectors to the ADC channel input.
- Options available with two isolated BNC connectors or two 2-contact LEMO connectors.



GENERAL DESCRIPTION

The SC25 is a two-channel direct-input card. It is packaged in a 3U (5.25") high, 220 mm (8.7") deep, module. In systems that include SC20 Bridge Signal Conditioner modules it may be necessary to provide some voltage-input channels. The SC25 serves this purpose by providing straight-through signal paths from the front-panel connectors to the ADC input channels. Options are available with two isolated BNC connectors or two 2-contact LEMO connectors.

RELATED PRODUCTS

- Model 5911 2-contact LEMO Cable Connector
- Model SC20 Wideband Bridge Signal Conditioner
- Model V710 Active Termination Panel

ORDERING INFORMATION

MODEL	DESCRIPTION
SC25-AA11	BNC Direct-input module
SC25-AB11	LEMO Direct-input module

Updated October 24, 2005

Copyright © 2005 KineticSystems Company, LLC. All rights reserved.

KineticSystems Company, LLC

900 N. State St.
Lockport, IL 60441-2200

Toll-Free (US and Canada):

phone 1-800-DATA NOW
1-800-328-2669

Direct:

phone +1-815-838-0005
fax +1-815-838-4424

Email:

mkt-info@kscorp.com

To find your local sales representative or distributor or to learn more about KineticSystems' products visit:

www.kscorp.com